

Cork Granules

Ecologic blond cork granules for thermal insulation of dry floors, suitable for wet environments

Specification



| THERMO-ACOUSTIC INSULATION BLOND CORK LOOSE GRANULES FOR DRY FLOORS, SUITABLE FOR WET AREAS

Supply and installation of the thermo-acoustic insulation of blond cork granules.

Cork granules is characterized by excellent values of thermal insulation and traspirability, and it is ideal for thermo-acoustic insulation and is also suitable for use in the presence of moisture.

The material is characterized by the following thermodynamic characteristics: density 200 kg/m³, coefficient of thermal conductivity $\lambda=0,037$ W/mK, specific heat $c=1674$ J/kg K, coefficient of resistance to vapor penetration $\mu=10 \div 13$ and fire resistant class 2, according to Circ. Min. Interno 14/09/1961, n. 91.

The granulometry of blond cork is mm.

Cork granules meets the requirements established for the release of the Certificate of Conformity to the criteria of Environmental Compatibility (CCA).

Head office:
Via Falcone e Borsellino, 58
I-50013 Campi Bisenzio (FI)

T: +39 055 8953144
F: +39 055 4640609

info@betonwood.com
www.betonwood.com

CRKG-IR.18.03



Member of
WWF
Global Forest &
Trade Network

Certified production
according to
ISO 9001:2008

